

Specifications — MKP 1000 Remote Control Keypads

Control/remote — keypad

Extron remote key pad control.. (2) 3.5 mm, 5-pole captive screw connectors

General

Power	Supplied by the matrix switcher or MCP 1000 Master
Temperature/humidity	Storage -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount	No, but furniture/wall mountable in a wall box
Enclosure type	Metal
Enclosure dimensions	
Plate	4.5" H x 4.6" W x 0.1" D (2 gang) (11.4 cm H x 11.7 cm W x 0.3 cm D)
Box	4.1" H x 4.1" W x 2.4" D (2 gang) 10.4 cm H x 10.4 cm W x 6.1 cm D
Boards	2.9" H x 3.5" W x 1.0" D (7.4 cm H x 8.9 cm W x 2.5 cm D) Allow at least 1" (2.5 cm) D for connectors and cable. (Depth excludes connectors.)
Product weight	
MKP 1000	0.3 lbs (0.1 kg)
MKP 1000WT	0.4 lbs (0.2 kg)
Shipping weight	
MKP 1000	2 lbs (1 kg)
MKP 1000WT	3 lbs (2 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL
Compliances	CE, FCC Class A
MTBF	30,000 hours
Warranty	3 years parts and labor

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

(7.51-082504-D4)